

KTAtaris

Metering Solution

CL740

THREE PHASE MULTI-FUNCTIONAL ELECTRICITY METER



CL740


CL740 is latest three phase multi-functional electricity meter designed for high accuracy and easy use, with tamper detection features and IEC62056-21 compliant communication ports. CL740 is used in a wide range of applications.

Standard features

- Energy Measurement
 - Measure total, forward, reverse active energy, reactive energy, and measure energy of 4-quadrant.
- Maximum Demand Measurement
- Multi-tariff
- Real-time Measurement
- Billing
- Event Log
- Tamper Detection
 - Power on/off
 - Terminal cover opening
 - Main cover opening
 - Reverse connection
 - Loss of phase
- Load Profile
- Optical, RS485 communication

CL740

Three Phase Electronic Energy Meter



Main Technical Parameter

Item	Parameter
Accuracy Class	1.0(Active); 2.0(Reactive)
Rate Voltage	3×240/415V
Nominal(Max) Current	Direct connected: 3×10 (100) A
Reference frequency	50Hz/60Hz
Working voltage range	0.70Un~1.30Un
Start current	0.001lb/0.004lb
V circuit power loss	≤1.5W 6VA
I circuit power loss	≤0.4VA
Display	LCD
Working temperature	-25~+65 °C
Limit temperature	-40~+70 °C
Storage and transportation temperature	-40~+70 °C
Average relative humidity	≤95%
protection rate	IP54
Designed life span	>15 years

Sole Distributor:

KINTA TERANG Sdn Bhd

5, Jln Pemberita U1/49, Temasya Industria Perk,

Glenmarie, 40150 Shah Alam, Selangor.

Tel: +603 5569 3241/4446

Fax: +603 5569 2731

Email: stcheah.kintaterang@gmail.com